

MINIKOTE LAMINATOR

School & Office



The MiniKote School & Office 25" • Item #201585

Providing Global Solutions For Identification & Lamination



This easy to operate, full featured, sleek, contemporary design is perfect for classroom and office environments. When your professional requirements demand a dependable, simple-to-operate laminator, Laminex meets those needs with our MiniKote Laminators. Offers the same dependable and reliable quality lamination as the Laminex AV Machines that have become so highly regarded for the past 50 years. Easily protects and preserves all your educational and professional documents including charts, posters, maps, newspaper clippings, teaching aids, children's drawings and more.

**Updated Design
Replaces AV Series**

**Same Dependable
Quality Lamination**

Ideal For Laminating

- Rules, Regulations & Procedures
- Attendance, Payroll, Records, Etc.
- Licenses & Certificates
- Schedules & Charts
- Magazine/Newspaper Articles
- Legal Documents
- Student/Employee Lists
- Display Signs
- Blueprints
- Labels
- Awards
- Diplomas
- Placemats
- Book Jackets
- Reports
- Contracts
- Corporate Records
- Photographs
- Flash Cards
- X-Rays
- Manuals
- Library Cards
- Transparencies
- ...and many more



844-443-7467 idshop.com



Hand Held Slitter with storage location on machine.

Footage Counter with digital display and reset easily tracks laminating film usage.



Keypad prevents unauthorized use.

Safety Shield prevents accidental contact with heated areas.

MiniKote School & Office

Standard Features

- **User Preset** Saves Speed And Temperature Settings Defined By The User
- **Factory Presets** Set A Speed And Temperature That Is Optimal For 1.5 Mil Permalam® Film (275°F) And 1.5 Mil Extralam® Film (225°F)
- **Footage Counter** With Reset Easily Tracks Laminating Film Usage
- **Hand Held Slitter** Convenient And Handy With Storage Right On The Machine
- **Adjustable Feedguide** Assures Exact Lamination
- **1" Mandrels Standard** (2 5/16" Supply Roll Mandrel Kit Optional)
- **Safety Shield** Prevents Accidental Contact With Heated Areas Of Machine
- **120V MiniKote Laminator** Accepts Standard Permalam® (homopolymer) Films In 1.5 and 3 Mil And 1.5 And 3 Mil Extralam® (copolymer) Films
- **240V MiniKote Laminator** Accepts Standard Permalam® (homopolymer) Films In 1.5, 3 and 5 Mil And 1.5, 3 And 5 Mil Extralam® (copolymer) Films
- **Keypad** Prevents Unauthorized Use Of The Laminator
- **Stop/Reverse** Button To Reverse The Machine
- **Digital Display** Will Show Temperature, Speed And Footage Counter
- **Temperature Controls** Increase And Decrease The Temperature In 1° Increments
- **Cooling Fans** Standard On 240V MiniKote. Two Built-In Fans On 18" 240V Machine Or Three Built-In Fans On 25" 240V Machine.
- **UL Listed**
- **CSA Approved, EU Approved**

Optional Features

- **Footswitch** For Hands Free Operation, Frees Hands For Guiding Materials During Lamination
- **Slitter Kit**, In-Line Slitter Allows Document Trimming During Lamination
- **Supply Roll Mandrel Kit** Allows The Machine To Accommodate 2 1/4" And 2 5/16" (LX) Core. Replaces Standard 1" Core.

Specifications

MINIKOTE 18" Item #201575 (120V)
School & Office Item #201580 (240V)

Height 15" Width 25" Depth (with feed tray) 20"
 Net Weight 50/52 Lbs. Shipping Weight 57 Lbs.
 Width of Lamination 18"
 Electrical: (120V) 120V AC, 60 Hz, 1400w
 (240V) 240V AC, 50 Hz, 1700w
 Color/Housing Red
 Standard Core 1"
 Speed 0 to 9.5 FPM (feet per minute)
 Film Accommodation 1.5 Mil & 3 Mil (5 Mil for 240V)
 (max. supply roll 1000' @ 1.5 Mil)

MINIKOTE 25" Item #201585 (120V)
School & Office Item #201590 (240V)

Height 15" Width 32" Depth (with feed tray) 20"
 Net Weight 65/68 Lbs. Shipping Weight 72 Lbs.
 Width of Lamination 25"
 Electrical: (120V) 120V AC, 60 Hz, 1400w
 (240V) 240V AC, 50 Hz, 2300w
 Color/Housing Red
 Standard Core 1"
 Speed 0 to 9.5 FPM (feet per minute)
 Film Accommodation 1.5 Mil & 3 Mil (5 Mil for 240V)
 (max. supply roll 1000' @ 1.5 Mil)

MINIKOTE 27" Item #201595 (120V)
School & Office (Not Available in 240V)

Height 15" Width 34" Depth (with feed tray) 20"
 Net Weight 66 Lbs. Shipping Weight 73 Lbs.
 Width of Lamination 27"
 Electrical: (120V) 120V AC, 60 Hz, 1400w
 Color/Housing Red
 Standard Core 1"
 Speed 0 to 9.5 FPM (feet per minute)
 Film Accommodation 1.5 Mil & 3 Mil
 (max. supply roll 1000' @ 1.5 Mil)

Metric Conversion Key

Dimension Height	15" = 381 mm	Shipping Weight	57 Lbs. = 25.6 K
Dimension Width	25" = 635 mm		72 Lbs. = 32.4 K
	32" = 812.8 mm		73 Lbs. = 32.8 K
	34" = 863.6 mm	Core Dimensions	1" = 25.4 mm
Dimension Depth	20" = 508 mm		2 1/4" = 57.15 mm
Lamination Width	18" = 457.2 mm		2 5/16" (LX) = 58.74 mm
	25" = 635 mm	Speed	0 to 9.5 FPM = 2.9 Meters
	27" = 685.8 mm		Per Minute
Net Weight	50 Lbs. = 22.5 K	Mil Thickness	1.5 Mil = 38.1 Microns
	52 Lbs. = 23.4 K	(1000' = 304 meters)	3.0 Mil = 76.2 Microns
	65 Lbs. = 29.2 K		5.0 Mil = 127.0 Microns
	66 Lbs. = 29.7 K		

For more information on the complete line of Laminex products including:

- ID Cards/Badges
- Video Identification Systems
- Desktop/Pouch Laminators
- Photo ID Systems/Supplies
- ID Accessories/Supplies
- Roll Laminators /Feeders/Cutters
- Laminating Films/Supplies

Call Toll Free: (800)438-8850

Products subject to change without notice.



A Laminex Company®

844-443-7467 idshop.com

Cat. #652506 (6/01)